

026 MASKING TAPE “PERFECT EDGE OUTDOOR”

Tape structure:

Backing: Japanese Washi paper

Adhesive: Acrylic water based

Product Description:

026 masking tape characterized by a smooth Washi paper backing and water based acrylic solvent free adhesive. It provides soft adhesion, sharp paint edges, good mechanical strength and clean removal after extremely long term UV and water exposure. Especially designed for outdoor precise painting operations in Painting and Marine industry.

Features:

- Sharp paint break-lines
- Resistant to moisture and most common water and solvent base paints
- 5 months outdoor UV resistance with clean removal
- Ideal for PVC, glass, wood, aluminum, plaster walls and Forex®
- Excellent paint anchorage

Technical information:

Properties	Units	Specification	Test method
Total weight	g/mm ²	82	ISO 536
Total thickness	mm	0.091	Internal
Peel adhesion	N/cm	1.2	AFERA 5001/PSTC 101
Tensile strength	N/cm	31	AFERA 5004/PSTC 131
Elongation at break	%	3.5	AFERA 5004/PSTC 131

Color: 

SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.



Main Application:

- Long term outdoor professional masking for painting operations in Painting and Marine industry
- Outdoor refinishing in Marine industry