

022 MASKING TAPE 80 °C

Tape structure:

Backing: Saturated crepe paper

Adhesive: Solvent borne rubber resin

Product Description:

022 temperature resistant masking tape characterized by a semi crepe paper backing and a solvent borne rubber resin adhesive. It is suitable for spray-painting operations with drying cycles at high temperatures up to 80°C (1 hour) in car refinishing application, performing in overlapping the tape, with masking paper and masking film with excellent holding power.

Features:

- Medium adhesion
- Excellent holding power
- Suitable for most common water and solvent base paints
- Clean removal after drying cycle at 80°C (1 hour)
- Clean removal after up to 7 days after application
- Excellent adhesion on painted metal, rubber and glass
- Quick stick
- Good paint anchorage

Technical information:

| Properties | Units | Specification | Test method |
|------------------------|-------------------|--------------------|---------------------|
| Total weight | g/mm ² | 92 | ISO 536 |
| Total thickness | mm | 0.12 | Internal |
| Peel adhesion | N/cm | 2.2 | AFERA 5001/PSTC 101 |
| Tensile strength | N/cm | 38 | AFERA 5004/PSTC 131 |
| Elongation at break | % | 7 | AFERA 5004/PSTC 131 |
| Temperature resistance | °C | up to +80 (1 hour) | |

Color:



SHELF LIFE AND STORAGE

Tapes should be used within 12 months when stored in original carton at 23 °C and max. 50 % relative humidity. We recommend a storage temperature between 15 and 25 °C. The product should not be directly exposed to heat or humidity. The product should be conditioned to room temperature before use

IMPORTANT NOTICE TO PURCHASER

All statements technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, users shall determine the suitability of the product for their intended use, and assume all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacture. Customers are advised to test the material to determine the suitability against intended applications.



Main Application:

- Professional masking for high temperature spray painting in Automotive refinishing industry.